



Specificaties

- Boringbereik 3 – 50
- Eenvoudig te installeren
- Geen as beschadiging
- Beschikbaar in blank staal (C45) en roestvrijstaal (1.4301)

Size	Dimensions (mm)			Clamping screw DIN 912		Weight m (g)
	d	D	L	M	T _A (Nm)	
3	3	16	9	M3 x 8	2.1	11
4	4	16	9	M3 x 8	2.1	11
5	5	16	9	M3 x 8	2.1	11
6	6	16	9	M3 x 8	2.1	10
7	7	18	9	M3 x 8	2.1	13
8	8	18	9	M3 x 8	2.1	12
9	9	24	9	M3 x 10	2.1	25
10	10	24	9	M3 x 10	2.1	24
11	11	28	11	M4 x 12	4.6	40
12	12	28	11	M4 x 12	4.6	39
13	13	30	11	M4 x 14	4.6	45
14	14	30	11	M4 x 14	4.6	43
15	15	34	13	M5 x 16	9.5	68
16	16	34	13	M5 x 16	9.5	65
17	17	36	13	M5 x 16	9.5	74
18	18	36	13	M5 x 16	9.5	71
19	19	40	15	M6 x 16	16	104
20	20	40	15	M6 x 16	16	101
21	21	42	15	M6 x 16	16	113
22	22	42	15	M6 x 16	16	107
23	23	45	15	M6 x 16	16	127
24	24	45	15	M6 x 16	16	122
25	25	45	15	M6 x 16	16	120
26	26	48	15	M6 x 16	16	139
28	28	48	15	M6 x 16	16	128
30	30	54	15	M6 x 18	16	171
32	32	54	15	M6 x 18	16	161
34	34	57	15	M6 x 18	16	181
35	35	57	15	M6 x 18	16	172
36	36	57	15	M6 x 18	16	169
38	38	60	15	M6 x 18	16	183
40	40	60	15	M6 x 18	16	172
42	42	73	19	M8 x 25	39	383
45	45	73	19	M8 x 25	39	360