



Specificaties

- Boringbereik 3 - 50
- Geen as beschadiging
- Beschikbaar in blank staal (C45) en roestvrijstaal (1.4301)

Size	Dimensions (mm)			Clamping screw DIN 912		Weight m [g]
	d	D	L	M	T _A (Nm)	
3	3	16	9	M3 x 8	2.1	11
4	4	16	9	M3 x 8	2.1	11
5	5	16	9	M3 x 8	2.1	10
6	6	16	9	M3 x 8	2.1	10
7	7	18	9	M3 x 8	2.1	13
8	8	18	9	M3 x 8	2.1	12
9	9	24	9	M3 x 10	2.1	23
10	10	24	9	M3 x 10	2.1	22
11	11	28	11	M4 x 12	4.6	39
12	12	28	11	M4 x 12	4.6	38
13	13	30	11	M4 x 14	4.6	43
14	14	30	11	M4 x 14	4.6	42
15	15	34	13	M5 x 16	9.5	65
16	16	34	13	M5 x 16	9.5	63
17	17	36	13	M5 x 16	9.5	72
18	18	36	13	M5 x 16	9.5	69
19	19	40	15	M6 x 16	16	100
20	20	40	15	M6 x 16	16	97
21	21	42	15	M6 x 16	16	107
22	22	42	15	M6 x 16	16	103
23	23	45	15	M6 x 16	16	122
24	24	45	15	M6 x 16	16	117
25	25	45	15	M6 x 16	16	114
26	26	48	15	M6 x 16	16	133
28	28	48	15	M6 x 16	16	123
30	30	54	15	M6 x 18	16	163
32	32	54	15	M6 x 18	16	156
34	34	57	15	M6 x 18	16	174
35	35	57	15	M6 x 18	16	171
36	36	57	15	M6 x 18	16	163
38	38	60	15	M6 x 18	16	178
40	40	60	15	M6 x 18	16	163
42	42	73	19	M8 x 25	39	367
45	45	73	19	M8 x 25	39	344
48	48	78	19	M8 x 25	39	392
50	50	78	19	M8 x 25	39	370